

# LED Downlights

Swap outdated CFL Lights with high quality LED Down Lights for long- lasting energy efficiency and instant brightness. Choose from a wide range of 3W to 40W



## Product Features

- Innumerable styles & Elegant appearance
- Non - Flickering
- Best Quality LED Chips from companies like CREE & SAMSUNG
- Premium Quality Power Driver with lowest power factor saver & high RA
- Easy Installation
- Varied finishes with strong die cast Aluminium body
- Low Maintenance
- All down lights come with premium quality power

## Applications

Residences, Showrooms, Hotels & Boutiques etc.

---



**Reflector Downlight**

**10W** VT-26101


- 1270 - 3000K Warm White
- 1271 - 4000K Day White
- 1272 - 6400K White

BOX QTY.

**27**


EAN Code

- 3800157611923
- 3800157611930
- 3800157611947



**120<sup>++</sup>**  
LM/W  
**HIGH LUMENS**

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 100-277V, 50/60Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>1200lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 135mm x 71mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø120mm</b>
PF	<b>&gt;0.5</b>		



**Reflector Downlight**

**20W** VT-26201


- 1273 - 3000K Warm White
- 1274 - 4000K Day White
- 1275 - 6400K White

BOX QTY.

**18**


EAN Code

- 3800157611954
- 3800157611961
- 3800157611978



**120<sup>++</sup>**  
LM/W  
**HIGH LUMENS**

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 100-277V, 50/60Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>2400lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 180mm x 83mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø167mm</b>
PF	<b>&gt;0.5</b>		



**Reflector Downlight**

**30W** VT-26301


- 1276 - 3000K Warm White
- 1277 - 4000K Day White
- 1278 - 6400K White

BOX QTY.

**12**


EAN Code

- 3800157611985
- 3800157611992
- 3800157612005



**120<sup>++</sup>**  
LM/W  
**HIGH LUMENS**

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 100-277V, 50/60Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>3600lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 220mm x 103mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø207mm</b>
PF	<b>&gt;0.9</b>		



**Reflector Downlight**

**40W** VT-26451


- 1279 - 4000K Day White

BOX QTY.

**12**


EAN Code

- 3800157612012



**120<sup>++</sup>**  
LM/W  
**HIGH LUMENS**

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 100-277V, 50/60Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>4800lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 220mm x 103mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø207mm</b>
PF	<b>&gt;0.9</b>		



**Reflector Downlight**


**10W** VT-2610

**1100 - 6400K White**


**BOX QTY.**  
**27**

EAN Code

3800230622372



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>730lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 135mm x 71mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø105mm</b>
PF	<b>&gt;0.5</b>		



**Reflector Downlight**


**20W** VT-2620

**1103 - 6400K White**


**BOX QTY.**  
**18**

EAN Code

3800230622402



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>1500lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 182mm x 90mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø160mm</b>
PF	<b>&gt;0.5</b>		



**Reflector Downlight**

**30W** VT-2630


**1106 - 4000K Day White**

BOX QTY.


**12**

EAN Code

3800230622433



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>2400lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 222mm x 111mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø205mm</b>
PF	<b>&gt; 0.9</b>		



**Reflector Downlight**

**40W** VT-2645


**1165 - 6400K White**

BOX QTY.


**12**

EAN Code

3800230627308



LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>120°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>PKW ( White)</b>
Luminous Flux:	<b>3200lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 222mm x 111mm</b>
CRI:	<b>≥80</b>	Cutting Size:	<b>Ø205mm</b>
PF	<b>&gt; 0.9</b>		



**COB Downlight**

**3W** VT-1123 RD

EAN Code

5098 - 3000K Warm White

3800157609401

5099 - 4500K Day White

3800157609418

5107 - 6000K White

3800157609425

BOX QTY.  
**100**

Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>60°</b>
Voltage/Frequency:	<b>AC: 85-265V, 50/60Hz</b>	Body Type:	<b>Aluminum</b>
Luminous Flux:	<b>200lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø45 x 35mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø36mm</b>
PF	<b>&gt;0.5</b>		



**COB Downlight**

**3W** VT-1123 SQ

EAN Code

5108 - 3000K Warm White

3800157609342

5109 - 4500K Day White

3800157609449

5110 - 6000K White

3800157609456

BOX QTY.  
**100**

Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>60°</b>
Voltage/Frequency:	<b>AC: 85-265V, 50/60Hz</b>	Body Type:	<b>Aluminum</b>
Luminous Flux:	<b>200lm</b>	Shape:	<b>Square</b>
LED Type:	<b>COB</b>	Dimension:	<b>45 x 45 x 35mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>36 x 36 mm</b>
PF	<b>&gt;0.5</b>		



**COB Downlight**

**3W** VT-1133 RD

EAN Code

5092 - 3000K Warm White

3800157609340

5093 - 4500K Day White


3800157609357

5094 - 6000K White

3800157609364

BOX QTY.  
**100**

Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>60°</b>
Voltage/Frequency:	<b>AC: 85-265V, 50/60Hz</b>	Body Type:	<b>Aluminum</b>
Luminous Flux:	<b>200lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø55 x 42mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø45mm</b>
PF	<b>&gt;0.5</b>		



**COB Downlight**

**3W** VT-1133 SQ

EAN Code

5095 - 3000K Warm White  
5096 - 4500K Day White  
5097 - 6000K White

3800157609371  
3800157609388  
3800157609395

BOX QTY.  
**100**

Sensor Compatible:	Yes	Beam Angle:	60°
Voltage/Frequency:	AC: 85-265V, 50/60Hz	Body Type:	Aluminum
Luminous Flux:	200lm	Shape:	Square
LED Type:	COB	Dimension:	55 x 55 x 42mm
CRI:	>80	Cutting Size:	45 x 45mm
PF	>0.5		




**COB Downlight**

**8W** VT-2908 RD

EAN Code

1118 - 6000K White

380023062516



BOX QTY.  
**50**

Sensor Compatible:	Yes	Beam Angle:	24°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Powder Coating Die cast
Luminous Flux:	550lm	Shape:	Round
LED Type:	COB	Dimension:	Ø103 x 75mm
CRI:	>80	Cutting Size:	Ø90mm
PF	>0.5		




**COB Downlight**

**8W** VT-2908 SQ

EAN Code

1113 - 3000K Warm White  
1115 - 6000K White

3800230625175  
3800230625199



BOX QTY.  
**50**

Sensor Compatible:	Yes	Beam Angle:	24°
Voltage/Frequency:	AC: 100-240V, 50/60Hz	Body Type:	Powder Coating Die cast
Luminous Flux:	550lm	Shape:	Square
LED Type:	COB	Dimension:	103 x 103 x 75mm
CRI:	>80	Cutting Size:	90 x 90mm
PF	>0.5		



**Zoom Light**

**30W** VT-2930



- 1306 - 3000K Warm White
- 1307 - 4500K Day White
- 1289 - 6000K White

BOX QTY.

**12**

EAN Code

- 3800157619936
- 3800157619943
- 3800157619646



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>99°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>Die Casting Aluminum</b>
Luminous Flux:	<b>2450lm</b>	Shape:	<b>Rectangle</b>
LED Type:	<b>COB</b>	Dimension:	<b>235 x 146 x 139mm</b>
CRI:	<b>≥80</b>	Cutting Size:	<b>220 x 132mm</b>
PF:	<b>&gt; 0.9</b>		



**Zoom Light**

**33W** VT-2933



- 1304 - 3000K Warm White
- 1305 - 4500K Day White
- 1288 - 6000K White

BOX QTY.

**20**

EAN Code


- 3800157619912
- 3800157619929
- 3800157619639



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>24°</b>
Voltage/Frequency:	<b>AC: 220-240V, 50Hz</b>	Body Type:	<b>Die Casting Aluminum</b>
Luminous Flux:	<b>2650lm</b>	Shape:	<b>Round</b>
LED Type:	<b>COB</b>	Dimension:	<b>Ø 165x140mm</b>
CRI:	<b>≥80</b>	Cutting Size:	<b>Ø 155</b>
PF:	<b>&gt; 0.9</b>		







**Step Light**

**3W** VT-1162

1327 - 3000K Warm White  
1326 - 4000K Day White


BOX QTY.

**50**  
EAN Code

3800157620550  
3800157620543



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>110lm</b>	Color of Fixture:	<b>White</b>
Body Type:	<b>PC</b>	Shape:	<b>Rectangle</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>230 x 80 x 28mm</b>



**Step Light**

**3W** VT-1162

1329 - 3000K Warm White  
1328 - 4000K Day White


BOX QTY.

**50**  
EAN Code

3800157620574  
3800157620567



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>110lm</b>	Color of Fixture:	<b>White</b>
Body Type:	<b>PC</b>	Shape:	<b>Rectangle</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>230 x 80 x 28mm</b>



**Step Light**

**3W** VT-1162

1331 - 3000K Warm White  
1330 - 4000K Day White

BOX QTY.

**50**  
EAN Code

3800157620598  
3800157620581



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>110lm</b>	Color of Fixture:	<b>White</b>
Body Type:	<b>PC</b>	Shape:	<b>Rectangle</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>230 x 80 x 28mm</b>



**Step Light**

**2W** VT-1142


**1315 - 3000K Warm White**  
**1314 - 4000K Day White**

**BOX QTY.**

**50**

EAN Code

3800157620437  
3800157620420



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>White</b>
Body Type:	<b>PC</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>ø150 x 27mm</b>



**Step Light**

**2W** VT-1142


**1317 - 3000K Warm White**  
**1316 - 4000K Day White**

**BOX QTY.**

**50**

EAN Code

3800157620451  
3800157620444



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>Black</b>
Body Type:	<b>PC</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>ø150 x 27mm</b>



**Step Light**

**2W** VT-1142


**1319 - 3000K Warm White**  
**1318 - 4000K Day White**

**BOX QTY.**


**50**

EAN Code

3800157620475  
3800157620468



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>Grey</b>
Body Type:	<b>PC</b>	Shape:	<b>Round</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>ø150 x 27mm</b>



**Step Light**

**2W** VT-1152


**1321 - 3000K Warm White**  
**1320 - 4000K Day White**

**BOX QTY.**

**50**

EAN Code

3800157620499  
3800157620482



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>White</b>
Body Type:	<b>PC</b>	Shape:	<b>Square</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>124 x 124 x 27mm</b>



**Step Light**

**2W** VT-1152


**1323 - 3000K Warm White**  
**1322 - 4000K Day White**

**BOX QTY.**


**50**

EAN Code

3800157620512  
3800157620505



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>Black</b>
Body Type:	<b>PC</b>	Shape:	<b>Square</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>124 x 124 x 27mm</b>



**Step Light**

**2W** VT-1152


**1325 - 3000K Warm White**  
**1324 - 4000K Day White**

**BOX QTY.**

**50**

EAN Code

3800157620536  
3800157620529



Sensor Compatible:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC100-240V, 50/60 Hz</b>	Beam Angle:	<b>55°</b>
Luminous Flux:	<b>60lm</b>	Color of Fixture:	<b>Grey</b>
Body Type:	<b>PC</b>	Shape:	<b>Square</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>124 x 124 x 27mm</b>

NEW



Step Light

3W VT-1172

1398 - 3000K Warm White  
1399 - 4000K Day White

EAN Code

3800157628310  
3800157628327

BOX QTY.



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	Black
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	151 x 72 x 154mm

NEW



Step Light

3W VT-1172

1400 - 3000K Warm White  
1401 - 4000K Day White

EAN Code

3800157628334  
3800157628341

BOX QTY.



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	Grey
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	151 x 72 x 154mm

NEW



Step Light

3W VT-1172

1402 - 3000K Warm White  
1403 - 4000K Day White

EAN Code

3800157628358  
3800157628365

BOX QTY.



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC:100-240V,50/60Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	White
Body Type:	PC	Shape:	Square
CRI:	>80	Dimension:	151 x 72 x 154mm

NEW



Step Light

3W VT-1182

1404 - 3000K Warm White  
1405 - 4000K Day White

EAN Code

3800157628372  
3800157628389

BOX QTY.

20



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	Black
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	Ø166 x 94mm

NEW



Step Light

3W VT-1182

1406 - 3000K Warm White  
1407 - 4000K Day White

EAN Code

3800157628396  
3800157628402

BOX QTY.

20



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	Grey
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	Ø166 x 94mm

NEW



Step Light

3W VT-1182

1408 - 3000K Warm White  
1409 - 4000K Day White

EAN Code

3800157628419  
3800157628426

BOX QTY.

20



Sensor Compatible:	Yes	PF:	>0.5
Voltage/Frequency:	AC100-240V, 50/60 Hz	Beam Angle:	90°
Luminous Flux:	210lm	Color of Fixture:	White
Body Type:	PC	Shape:	Round
CRI:	>80	Dimension:	Ø166 x 94mm




**Step Light**

**3W** VT-1109 RD


1207 - 3000K Warm White  
1208 - 4200K Day White

BOX QTY.  
**100**


EAN Code  
3800157600231  
3800157600248



**LUMINOUS INTENSITY DISTRIBUTION**



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>15°</b>
Voltage/Frequency:	<b>AC: 100-240V, 50/60Hz</b>	Color of Fixture:	<b>PKW (White)</b>
Luminous Flux:	<b>120lm</b>	Shape:	<b>Round</b>
Body Type:	<b>Aluminum</b>	Dimension:	<b>Ø80 x 51mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>Ø62mm</b>
PF:	<b>&gt;0.5</b>		




**Step Light**

**3W** VT-1109 SQ


1209 - 3000K Warm White  
1210 - 4200K Day White  
1223 - 6000K White

BOX QTY.  
**100**

EAN Code  
3800157600255  
3800157600262  
3800157601504



**LUMINOUS INTENSITY DISTRIBUTION**



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>15°</b>
Voltage/Frequency:	<b>AC: 100-240V, 50/60Hz</b>	Color of Fixture:	<b>PKW ( White)</b>
Luminous Flux:	<b>120lm</b>	Shape:	<b>Square</b>
Body Type:	<b>Aluminum</b>	Dimension:	<b>80 x 80 x 51mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>62 x 62mm</b>
PF:	<b>&gt;0.5</b>		



**Step Light with Sensor**


**BOX QTY.**  
**100**

**3W** VT-8035

EAN Code

**5570 - 4000K Day White**

3800157617291



Sensor Included:	<b>Yes</b>	PF:	<b>&gt;0.5</b>
Voltage/Frequency:	<b>AC:100-240V, 50/60Hz</b>	Beam Angle:	<b>45°</b>
Luminous Flux:	<b>100lm</b>	Color of Fixture:	<b>Plastic</b>
Body Type:	<b>Die cast Aluminum</b>	Shape:	<b>Square</b>
CRI:	<b>&gt;80</b>	Dimension:	<b>85 x 85 x 42mm</b>



**Step Light**


**BOX QTY.**  
**100**

**3W** VT-1143

EAN Code

**1284 - 4000K Day White**

3800157617307



Sensor Compatible:	<b>Yes</b>	Beam Angle:	<b>83°</b>
Voltage/Frequency:	<b>AC: 85-265V, 50/60Hz</b>	Color of Fixture:	<b>PKW ( White)</b>
Luminous Flux:	<b>100lm</b>	Shape:	<b>Square</b>
Body Type:	<b>Die cast Aluminum</b>	Dimension:	<b>84 x 84 x 43mm</b>
CRI:	<b>&gt;80</b>	Cutting Size:	<b>72 x 72mm</b>
PF:	<b>&gt;0.5</b>		